



Cosmos Lac AE

1 Pindou str.

17672 Kallithea, Athens, Greece.

Tel.: +30 2109570222 -

Fax: +30 2109566671

factory@cosmoslac.com

www.cosmoslac.com

Technical Data Sheet

PRODUCT	COSMOS LAC EASY MAX
DESCRIPTION	Fast drying acrylic paint in aerosol, with high coverage and excellent adhesion. With 2 caps for wide and narrow spray.
USES	Ideal for metal, wood and plastic surfaces.
Viscosity	18-25 sec (Flow Cup DIN4, 20°C)
Density	0,8 – 1,1 g/L (Density Cup 100cm ³ /20°C, ASTM D – 1475)
Solids w/w	20-25%
VOC content	640 g/L
Flash Point	-104 °C (based on propellant)
Drying time	Touch (20°C, Humidity<65%): 5-10min Through dry (20°C, Humidity <65%) : 1h Maximum hardness: 24 hours
Coverage	4m ² / 400mL
Gloss	3-8 (60°)
Film thickness	200µm (wet), 50-100µm (dry)
Can Pressure	4bar (20 °C) , 8 bar (50 °C)
Contents	400ml
Application	Clean the surface from dust, grease, rust etc. Mask the area if necessary. Shake well for 2-3 minutes. Check the product on a test surface. Spray close to the surface (10-15 cm). For best results apply 2 coats with 10' interval. Best application temperature : 20 °C - 25 °C
After use	Spray holding the can inverted for 3". Clean the caps with solvent.
Storage	5-35°C. Do not put in vehicles.

ISSUED : 20 February 2017, factory@cosmoslac.com