



# 333 RENOVATION PERFECTION Kitchen



**Household appliances**  
Stainless steel, metal, plastic

**Worktops**  
Varnished woods, melamine, laminates, tiles

**Sideboard**  
Tiles, glass, stainless steel

**Kitchen furniture**  
Raw, varnished, painted woods, melamine

## PROPERTIES

Renovation Perfection paint has been specially designed to durably renew highly stressed surfaces and materials. Thanks to the combination of specific polymers and the Additiv System, a real booster of performance, it offers a high quality finish, ready to face all the hazards of everyday life.

## THE PAINT TO RENOVATE YOUR KITCHEN



- Direct to furniture, worktops, sideboards
- High resistance to scratches and impact

Sizes : Tester 75ml – 750ml

## COLOURCHART





RENOVATION  
PERFECTION

# Kitchen

## INFOS:

750ml = +/- 10sqm  
= 5sqm with 2 coats

**6h** Recoat

**Water** Tool cleaning

**24h** Fully dry

## TOOLS :



**Wide stick or  
Paint stirrer**



**Round edged paint brush**  
(for angles, corners & finishes)



**4-5mm short pile roller**

## PREPARATION

**PREPARATION of the surface is ESSENTIAL.**

**WASHING the surface with a soda-based or sugar soap (alkaline) cleaner is CRUCIAL..**

Remove any silicone sealant before painting. Reseal after application of the paint.

- RAW / POROUS SURFACES (wood, mdf): lightly sand and remove dust.
- On raw oak and chestnut, first apply a suitable undercoat to block the tannins.
- On already painted or varnished surfaces: wash, rinse thoroughly with water, leave to dry, then lightly sand with 240 grit sandpaper and remove dust.
- On non-painted surfaces (wall tiles, stainless steel, glass, laminates): wash, rinse thoroughly with water then leave to dry.

## APPLICATION

Apply the paint at room temperature between 12 and 25°C and avoid draughts.

1. Empty the Additiv System (the sachet that is placed under the lid of the tin) into the paint. Stir the paint for 5 minutes, working around the bottom of the tin with a wide stick to mix it well.
2. Work on small surfaces. Apply from one end to the other. Follow with successive cross strokes. Leave to dry for 6h and apply a 2nd coat in the same way.

On horizontal surfaces, the paint has to be covered with the Renovation Perfection worktop varnish.

Once the sachet has been added, the mixture must be used within less than 10 days to maintain optimal adhesion and performance.

### V33 TIPS

- To clean your painted surfaces, use a gentle detergent and a non-abrasive sponge.
- Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the rst 20 days after application.

**HEALTH AND SAFETY** : Contains biocidal products (preservatives) : contains C(M)IT/MIT (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j - Two-pack reactive performance coatings for specific end use such as floors) : 140g/L (2010). This product contains max 29g/L VOC .