



RENOVATION
PERFECTION

Sanitaryware



DESTINATION

Bathtub, shower tray

Porcelain enamelled, ceramic, cast iron, enamelled steel, acrylic resin

Wash basin, bidet

Porcelain enamelled, ceramic, cast iron, enamelled steel, acrylic resin

PROPERTIES

Renovation Perfection paint + protection have been specially designed to durably renew highly stressed surfaces and materials. Thanks to the combination of specific polymers and the Additiv System, a real booster of performance, it offers a high quality finish, ready to face all the hazards of everyday life.

A PERFORMING SYSTEM TO RENOVATE YOUR SANITARYWARE



Size : 2 x 0,5L



- Directly on bathtub, sink, shower tray
- High resistance to repeated immersion

COLOURCHART

SATIN

White



Sanitaryware



Recoat



Tool cleaning



Fully dry

TOOLS:



- **MINI-ROLLER high density foam** (for curved surfaces)
- **ROLLER lacquer** (for large flat surfaces)



Wide stick or Paint stirrer



Round edged paint brush (for angles, corners & finishes)

PREPARATION

Remove any silicone sealant before painting. Reseal after application of the paint. The support has to be clean, dry and non-greasy. the surface with a soda-based or sugar soap (alkaline) cleaner. Rinse very carefully with water then leave to dry.

APPLICATION OF THE PAINT

Empty the Additiv System (the sachet that is placed under the lid of the tin) into the paint. Stir the paint for 5 minutes, working around the bottom of the tin with a wide stick to mix it well. Disassemble the taps and / or apply masking tape on the areas to be protected.

Remove areas of difficult access or around metal accessories with a brush. Apply the first layer to the foam roller, starting at the bottom and then up to the edges, working in strips of about 15 cm. Do not start 2nd coat while it's still drying. The painting may not be very covering, but the final result can be assessed in 2 layers. Remove the masking tape and allow to dry for 8 hours. Apply the same principle to your second coat and allow to dry for 8 hours before applying the protector.

APPLICATION OF THE PROTECTION

Empty the Additiv System* (the sachet that is placed under the lid of the tin) into the paint. Stir the paint for 5 minutes, working around the bottom of the tin with a wide stick to mix it well. Apply from one end to the other. Follow with successive cross strokes. Leave to dry for 8h and apply a 2nd coat in the same way. It will be necessary to wait 7 days of drying before re-using your sanitary (immersion water, cleaning products).

**Once the sachet has been added, the mixture must be used within less than 10 days to maintain optimal adhesion and performance*

V33 TIPS

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

HEALTH AND SAFETY - V33 PAINT

Contains biocidal products (preservatives): contains C(M)IT/MIT (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j - Two-pack reactive performance coatings for specific end use such as floors): 140g/L (2010). This product contains max 4g/L VOC.

HEALTH AND SAFETY - V33 PROTECTOR

Contains biocidal products (preservatives): contains C(M)IT/MIT (3:1); 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. EU limit value for this product (cat A/j - Two-pack reactive performance coatings for specific end use such as floors): 140g/L (2010). This product contains max 52g/L VOC..