



## V33 BOAT VARNISH



Waterproof – Anti abrasion  
Clear gloss

### **Destination**

Suitable for all types of wood, European and exotic.  
Recommended for external woodwork subject to difficult exposure: boat bridges, gateways, seaside house doors and windows, terraces, balconies...

### **Characteristics**

This Marine Varnish, based on polyurethane resins and anti-UV gives optimal protection to your outdoor window and door frames, subject to marine climates and heavy exposure to the sun.

Its formulation makes it absolutely watertight and resistant to sea salts.

Its strong abrasion-resistance means it can be applied in outdoor passageways: terraces, balconies, outdoor stairways...

### **Surface preparation**

**NEW WOOD:** Brush and remove dust. Dilute the 1st coat with 10% White Spirit.

**VARNISHED WOOD:** Carefully sand using fine grit paper (240). If the varnish has scaled, strip it using V33 Special Wood Stripper. Rinse with water or V33 Cleaning Solvent. Leave to dry for 24 H.

## **Application**

Stir well before use.

Apply with a flat brush or spray gun (dilute with 10% White spirit) in two coats on clean, dry and completely degreased wood.

Leave the 1st coat to dry for 6 hours.

Sand lightly with fine glass paper (240) and dust before applying the second coat.

## **Tips for application**

Ideal conditions for application: 12 to 15°C in dry weather.

You are recommended to degrease oily wood before applying the varnish, using V33 Cleaning Solvent.

You are recommended to slightly round the corners of your woodwork with glass paper, to ensure an even coating of varnish.

## **Properties**

Finish	gloss	
Shades	clear	
Packaging	France	0,5L – 1L – 2,5L
	Export	0.75L - 2.5L
Drying	Drying time to recoat: 6 h	
	Complete drying time: 24 h	

Drying may be affected by the temperature of application and substances in the wood.

Performance in 1 coat per 1L: 12 m<sup>2</sup>

Performance may vary according to the type of wood and its condition.

Cleaning white spirit or V33 cleaning solvent

Application brush or spray-gun (dilute with 10 to 15% white spirit)

## **SAFETY RECOMMENDATION AND PRECAUTIONS FOR USE**

### **WARNING**

**DO NOT ALLOW TO FREEZE**

Contains Naphtha, hydrotreated heavy.

EUH208: Contains ethylmethyletoxime. May produce an allergic reaction. H226:

Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand. P102: Keep

out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271: Use only outdoors

or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority).

EU limit value for this product (cat. A/e): 400g/l (2010). This product contains max 400g/l VOC.

NOVENTA A.E  
Πεθύμνου 1  
106 82 Αθήνα  
Τél : 210 – 8218502

G.S. Hadjiyiannis Logistics Ltd  
PO Box 55004  
3820 Limassol - Cyprus  
Τél : +357-25-877430

[www.v33.com](http://www.v33.com)