RUST-OLEUM®

## **Technical Data Sheet**

Rust-Oleum Metallic Furniture Paint

An elegant metallic paint. Can be used as a basecoat in combination with Rust-Oleum Chalky Finish Furniture Paint to achieve a luxurious, distressed effect or use as a top coat for a pure metallic finish. No priming or sanding necessary on most surfaces (Simply ensure surfaces are smooth, dry and free from contaminants).

**Preparation:** For best results, ensure surface is smooth, clean, dry and free from wax, polish, oil or any other surface contaminants. If wax or polish has been used clean the surface thoroughly with white spirit. We recommend that bare wood should be sanded before painting.

**Application:** Stir thoroughly prior to use. The product may be applied by brush or roller. If applying by brush, apply evenly following the grain of the wood. If rollering, use a short nap mohair roller. To create a distressed look apply Rust-Oleum Metallic Finish Furniture Paint, allow to dry then apply a coat of Rust-Oleum Chalky Finish Furniture Paint. Allow to dry then lightly abrade with moistened sand paper or a stainless steel scouring pad - abrade with the grain of the wood. Protect the paint effect with Rust-Oleum Furniture Finishing Wax or Rust-Oleum Furniture Lacquer.

**Coverage:** Up to 14m2 / litre. Coverage may vary depending upon method and rate of application and porosity of surface.

**Drying Time:** Touch dry in 1 hour. Handle after 4 hours. Recoat after 4 hours. Full hardness after 4 hours.

Clean Up: Remove as much product as possible from application equipment before washing with water. Do not empty into drains or

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK. **Technical Services Department: 0191 410 6611** 

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Limitations:** Not for use directly onto metal. Not a stain-blocking product. Prime any surfaces where stain-bleed may be an issue, including knots with an appropriate stain blocking primer. If unsure, test on an inconspicuous area before painting. Not recommended for outdoor use. Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.

**Shelf Life:** 2 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.

Product VOC = 25 g / litre max.