

# Technical Data Sheet

Rust-Oleum Furniture Finishing Wax

---

**Rust-Oleum Furniture Finishing Wax is a clear, colourless wax polish that should be used to protect the finish achieved with Rust-Oleum Furniture Paint. It is easy to apply by brush or rag and dries with a soft, velvety sheen. The wax finish ensures the paint finish is water-repellent and seals against stains and marks.**

**Preparation:** To be applied over Rust-Oleum Furniture Paint. Ensure surface to be coated is clean, dry, sound and free from contamination.

**Application:** Apply sparingly in small areas at a time with a brush or soft cloth. Allow to dry for 10 minutes then buff with a soft cloth to the desired sheen level. To obtain a higher sheen level apply a second coat.

**Coverage:** Up to 14m<sup>2</sup> / litre. Coverage may vary depending upon method and rate of application and porosity of surface.

**Drying Time:** Dry in 15 minutes.

**Clean Up:** Remove as much product as possible from application equipment before washing with hot soapy water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Shelf Life:** 2 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.  
**Technical Services Department: 0191 410 6611**  
E-mail: [info@tor-coatings.com](mailto:info@tor-coatings.com) [www.tor-coatings.com](http://www.tor-coatings.com) or [www.rustoleumspraypaint.com](http://www.rustoleumspraypaint.com)

warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.

Product VOC = 610 g / litre.