

Visto Ready Smooth

Ready to use finishing putty



Ready to use white fine-grained finishing putty of large surfaces in paste, suitable for interior walls and ceilings of plaster, gypsum board and concrete surfaces where perfect surface finishing (with bright lighting, decoration styles, etc) is required. It dries quickly and sanded very easily creating a very smooth, uniform and cohesive surface paintable with emulsion or enamel paints. It can be applied even in very thin layer.

Certified with the CE Marking according to EN 13963.

- Very smooth
- Easy workability & sanding

COLOURS

Available in white.

PACKAGING

Pails	5 Kg	18 Kg
-------	------	-------

SPREADING RATE

1 Kg/m² for at 0,5 mm thickness.

SURFACE PREPARATION

Surfaces must be clean, dry and smooth, free from dust, grease, loose material.

APPLICATION

Apply using a spatula/knife or airless spray in one or two layers. Sanded after 3-4 hours with sandpaper and once cleaned, primed and then painted with any emulsion or enamel paint of Vitex. Do not apply at temperature below 5°C, above 35°C and / or relative humidity above 80%.

It is touch dry in 2-3 hours. The second layer is applied after 4-6 hours. Drying time depends on film thickness and weather conditions (humidity and temperature).

Tools must be cleaned immediately after use with water and if needed with soapy water or a detergent.



TECHNICAL CHARACTERISTICS

Viscosity	200.000 ± 75.000 cP (BROOKFIELD, 25°C)
-----------	---

STORAGE

Containers must be kept closed in a cool, dry, well ventilated area protected from direct sunlight at temperatures between 5°C - 38°C.

SAFETY ADVICE

Read label before use. For further instructions - precautions see Material Safety Data Sheet.



T.Θ. 139 Ημερος Τόπος, Ασπρόπυργος Τ.Κ. 193 00
P.O. Box 139 Imeros Topos, Aspropyrgos GR 193 00
T. + 30 210 5589 500, F. + 30 210 4835 007, www.vitex.gr