

DIAXYL DECOR WB

Water-based Wood Stain

Protective and decorative water-based penetration varnish for interior and exterior wooden surfaces. Due to its special formulation prevents effectively the growth of mould and fungi in the film. Highlights the wood grain and enhances its natural beauty. It penetrates deeply through the wood pores protecting it from moisture and UV radiation.



Paints with
UV filters
for protection
from
sunlight

Advantages:

- Enriched with UV filters for excellent resistance to UV radiation
- Enhances natural wood texture

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

15 - 30 sec (FORD CUP#4, 25°C)

Density

1,03 ± 0,02 Kg / L (ISO 2811)

FINISH

Natural

Satin

Gloss



Natural Finish

DILUTION




Undiluted

Ready for use

COLOURS

11 ready-made
shades




COVERAGE



One coat

12-16 m²/L



Two coats

6-8 m²/L

DRYING TIME



Touch dry

1-2 h

Recoat

10-12 h

COLOR CARDS - FANDECKS



PACKAGING

11 Ready-made Shades

750 mL

2.5 L



WOOD PROTECTION

APPLICATION

APPLICATION FIELD

For interior and exterior wooden surfaces.

PREPARATION



Surfaces should be smooth, clean, dry, free from grease, rosins or old varnishes.



On new wooden surfaces apply preservative Diaxyl Extra water-based for protection against fungi and insects.



STEPS

1 Stir well before use.

2 Apply the first coat by brush, roller or spray gun.

3 Recoat, if desired, after 10-12 hours.

TIPS

- Application at 5-35°C and <80% RH and wood moisture should not exceed 18%.
- The final shade of the wooden surface depends on the natural colour and absorbency of the wood, as well as the number of coats of Diaxyl Decor.
- Tools must be cleaned immediately after

use with water and if needed, with soapy water or detergent.

- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.

- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Interior and exterior minimal build woodstains", VOC content limit **130 g/L**. Maximum VOC content **29 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C

Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

