

# VITO ACRYLIC

## Acrylic Paint

Acrylic paint for exterior use, based on acrylic copolymer resins. It exhibits great hiding power and high spreading capacity. It has very good levelling properties and produces a smooth flat surface. Vito Acrylic is certified from the University of Athens, department of Physics as a cool paint characterized by high solar reflectance value (SR), high infrared emittance ( $\epsilon$ ) and high reflectance index value (SRI).



Cool Paint

**Advantages:**

- High performance and coverage
- Very good workability and easy application
- Certified cool paint

### PRODUCT FEATURES

#### TECHNICAL CHARACTERISTICS

**Viscosity**

110 ± 10 KU (ASTM D 562, 25°C)




**Density**

1,59 ± 0,02 Kg / L (ISO 2811) for white

**Gloss**

< 5 units @ 60° (ISO 2813)

#### COVERAGE



**One coat**

10-12 m<sup>2</sup>/L



**Two coats**

5-6 m<sup>2</sup>/L

#### PACKAGING

White	3 L	9 L	15 L
Bases	1 L	3 L	9 L

#### FINISH

Mat	Satin	Gloss
✓		

Mat Finish

#### DILUTION



**Water**

8-10 %

#### DRYING TIME



**Touch dry**

30-60 min

**Recoat**

3-4 h

#### COLOURS

**3000 +**

White and unlimited number of shadesthrough **Vitex Coloring System**



#### COLOR CARDS - FANDECKS



# EXTERIOR USE

## APPLICATION

### APPLICATION FIELD

For all new or old surfaces such as plaster, concrete or spatula surfaces, after proper preparation.

### PREPARATION



**Surfaces** should be clean, dry and smooth, free from dust, grease and loose or flaking paint.

**To fill** any cracks or holes use Acrylic Putty.



**Surfaces previously covered with water paints or distempers** (lime wash or ceiling white) should be primed with Acrylan Unco Eco, Durovit or Vitosin.



**New surfaces** made of plaster, concrete, cement, plasterboard, etc. should be first primed with Acrylan Unco Eco or Durovit.



### STEPS

- 1 Dilute 8-10% with water and stir well before use.
- 2 Apply the first coat by brush, roller or airless spray gun.
- 3 Recoat after 3-4 hours.

### TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Allow new plaster or concrete surfaces to cure a minimum of 30 days prior to paint application.
- The product must be exclusively tinted through **Vitex Coloring** System in the recommended base.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces with Vito Acrylic. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.
- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating how much paint you will need.
- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

## ADDITIONAL INFORMATION

### VOCs (Volatile Organic Compounds)



"Exterior walls of mineral substrate". VOC content limit **40 g/L**. Maximum VOC content **29 g/L** VOCs (ready for use product).

### PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

### STORAGE



**5°C-38°C**  
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

**+30.210.5589.400**  
TECHNICAL SUPPORT

**ISO 9001**  
14001  
CERTIFIED 45001

