

Additive for tile adhesives and joint grouts

Description

DS-99 is a polymer-based admixture for tile adhesives and grouts, offering significant improvements of their properties:

- Increases bonding to the substrate.
- Increases flexural and compressive strength.
- Improves flexibility.
- Increases impressively abrasion resistance.
- Offers water impermeability.
- Improves chemical resistance.

Fields of application

DS-99 is used as an admixture for tile adhesives and grouts, in cases of high demand for water impermeability, mechanical strength and chemical resistance.

Technical data

Color: white
Density: 0,99 - 1,01 kg/lit
Application temperature: between +5°C and +30°C

Directions for use

The mixing water of tile adhesives or grouts is replaced with a mixture of DS-99 and water, in proportions of 1:1 up to 1:2 by volume.

Packaging

DS-99 is supplied in plastic containers of 1 kg, 5 kg and 20 kg.

Shelf-life - Storage

12 months from production date if stored in original, unopened packaging, in temperature between +5°C and +35°C. Protect from direct sun exposure and frost.

Remarks

- Should be thoroughly stirred before use.

ISOMAT S.A.
BUILDING CHEMICALS AND MORTARS
MAIN OFFICES - FACTORY:
17th km Thessaloniki - Ag. Athanasios Road,
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece,
Tel.: +30 2310 576 000, Fax: +30 2310 722 475
www.isomat.net e-mail: info@isomat.net