

tesa® Professional 60101 Fibreglass tape



Product Information

Fibreglass Tape

tesa® 60101 self-adhesive fibreglass tape features the state of the art in joint tape technology. With its very strong and flat fibreglass mesh, tesa® 60101 offers durable and long lasting drywall/plaster board joints. The excellent adhesion and the very good tensile strength allow one-time application and smooth finished joints.

Main Application

tesa® 60101 is also used for fixing and patching small holes and cracks.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	fibreglass	• Type of adhesive	acrylic
• Color	white	• Elongation at break	5 %
• Total thickness	185 µm	• Tensile strength	50 N/cm

Adhesion to

- | | |
|---------|----------|
| • steel | 0.5 N/cm |
|---------|----------|

Properties

- | | | | |
|-------------------------------|------|------------------|------|
| • Suitable for rough surfaces | ●●●● | • Conformability | ●●●● |
|-------------------------------|------|------------------|------|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=60101>